


Kap 80 Surface Square Optic Flood

■ ■ 03.6053.14 - Black/Black

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Non dimmable 110/240V.




Main specifications

| | | | |
|------------------------|-----------------|--------------------|--------|
| Number of heads | 1 | Environment | Indoor |
| Lamp category | LED | | |
| Power (W) | 9.2W | | |
| Net lumen (lm) | 640 | | |
| Mountings | Ceiling surface | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 55 |
| Beam angle C90-270 (°) | 56 |



Beam Angle: 55°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 853 | 1.05 |
| 2 | 213 | 2.10 |
| 3 | 95 | 3.16 |
| 4 | 53 | 4.21 |
| 5 | 34 | 5.26 |

Luminous flux luminaire
640 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 18.20 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Electronic | | |

Physical

| | |
|--------------------|-------------|
| Color | Black/Black |
| Orientation | Fixed |
| Weight (kg) | 0.45 |

