

Kap 80 Surface Square Optic Medium Dali/Push Version

03.6011.18.DA - Deep Brown/Gold

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Dali/Push dimming 220/240V.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 600 |
| Lamp category | LED | Mountings | Ceiling surface |
| Power (W) | 9.2W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 25 |
| Beam angle C90-270 (°) | 27 |



| | | | |
|--------------------|-------------|--------------|-------------|
| Beam Angle: | 25° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 1672 | 0.45 | |
| 2 | 418 | 0.90 | |
| 3 | 186 | 1.34 | |
| 4 | 104 | 1.79 | |
| 5 | 67 | 2.24 | |

Luminous flux luminaire
600 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|---------------------------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 18.20 | Insulation class | I |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Dimmable Push, Dimmable DALI | | |
| | 1 | | |

Physical

| | |
|--------------------|--------------------|
| Color | Deep Brown/Gold |
| Orientation | Fixed |
| Weight (kg) | 0.45 |

