

## Kap 80 Surface Square Optic Medium Dali/Push Version

03.6012.B1.DA - White/Copper

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body.  
Dali/Push dimming 220/240V.




### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 639                 |
| Lamp category   | LED   | Mountings      | Ceiling surface     |
| Power (W)       | 9.2W  | Environment    | Indoor dry location |
| CCT (K)         | 2700K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 26        |
| Beam angle C90-270 (°) | 26        |



Beam Angle: 26°

h(m) E(lx) D(m)

1 1800 0.46

2 450 0.93

3 200 1.39

4 112 1.86

5 72 2.32

Luminous flux luminaire  
639 lm (EXTREME CUT OFF)

### Electrical

|                |                                 |                  |         |
|----------------|---------------------------------|------------------|---------|
| Frequency (Hz) | 50/60                           | Emergency        | Without |
| Voltage (V)    | 18.20                           | Insulation class | I       |
| Dimmable       | Yes                             |                  |         |
| Driver         | Integrated                      |                  |         |
| Driver type    | Dimmable Push,<br>Dimmable DALI |                  |         |
|                | 1                               |                  |         |

### Physical

|             |              |
|-------------|--------------|
| Color       | White/Copper |
| Orientation | Fixed        |
| Weight (kg) | 0.45         |

