

Kap 80 Surface Square Optic Spot

03.6032.B1 - White/Copper

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Non dimmable 110/240V.




Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 710 |
| Lamp category | LED | Mountings | Ceiling surface |
| Power (W) | 9.2W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 18 |
| Beam angle C90-270 (°) | 19 |



Beam Angle: 18°

h(m) E(lx) D(m)

1 2770 0.31

2 693 0.62

3 308 0.94

4 173 1.25

5 111 1.56

Luminous flux luminaire
710 lm (EXTREME CUT OFF)

Electrical

| | | | |
|----------------|--------------|------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 18.20 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Non Dimmable | | |

Physical

| | |
|-------------|--------------|
| Color | White/Copper |
| Orientation | Fixed |
| Weight (kg) | 0.45 |

