

## Kap Ø 105 Deep

■ 05.7151.GL - Gold

Recessed luminaire with LED light source. Remote electronic transformer 220/240V not included. Pre-installation frame. To be ordered separately.


Recessed luminaire with LED light source. Remote electronic transformer 220/240V not included. Pre-installation frame. To be ordered separately.

### Main specifications

<b>Number of heads</b>	1	<b>CRI</b>	90
<b>Lamp category</b>	LED	<b>Net lumen (lm)</b>	1459
<b>Power (W)</b>	23W	<b>Mountings</b>	Ceiling recessed
<b>System power (W)</b>	25.9	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	23
<b>Beam angle C90-270 (°)</b>	23
<b>Efficiency (lm/W)</b>	38



<b>Beam Angle:</b>	23°	
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	7725	0.42
2	1931	0.83
3	858	1.25
4	483	1.66
5	309	2.08

Luminous flux luminaire  
1459 lm (EXTREME CUT OFF)

### Electrical

<b>Voltage (V)</b>	34	<b>Emergency</b>	Without
<b>Current (mA)</b>	650	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		

### Physical

<b>Color</b>	Gold
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	190
<b>Weight (kg)</b>	0,48
<b>Spot diameter (mm)</b>	106

## Kap Ø 105 Deep



---

Continuous current power supply, 0/1-10V dimmable, 220/240V – 50/60Hz, 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/1000/1050mA-36W.  
60.9439



---

Continuous current supply source 240V – 50/60Hz with dimmable DALI 2, push dimming. 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/1000/1050mA-36W  
60.9186



---

Continuous current power supply, dimmable Casambi, 220/240V – 50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W  
60.9207



---

Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch. 350mA – 15W / 400mA – 17W / 450mA – 19W / 500mA – 22W / 550mA – 24W / 600mA – 26W / 650mA – 28W / 700mA – 30W no regulable  
60.9592



---

Installation can for concrete  
08.8420.00



---

Installation frame No Trim  
08.9104.00