


\*NO TRIM  
\*\*TRIM



## Kap Ø 145 Deep

03.4497.CUB - Copper


Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.

### Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 98                  |
| Lamp category    | LED   | Net lumen (lm) | 662                 |
| Power (W)        | 17W   | Mountings      | Ceiling recessed    |
| System power (W) | 17    | Environment    | Indoor dry location |
| CCT (K)          | 2700K |                |                     |

### Optical

|                        |              |
|------------------------|--------------|
| Lighting type          | Direct       |
| LED type               | Phosphor LED |
| Light distribution     | Symmetric    |
| Optical type           | Medium       |
| Beam angle (°)         | 28           |
| Beam angle C90-270 (°) | 28           |
| UGRL                   | 3            |
| Efficiency (lm/W)      | 38           |



Beam Angle: 28°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2253  | 0.50 |
| 2    | 563   | 1.01 |
| 3    | 250   | 1.51 |
| 4    | 141   | 2.02 |
| 5    | 90    | 2.52 |

Luminous flux luminaire  
662 lm (EXTREME CUT OFF)

### Electrical

|                |                 |                  |              |
|----------------|-----------------|------------------|--------------|
| Frequency (Hz) | 50/60           | Driver type      | Non Dimmable |
| Voltage (V)    | 22              | Emergency        | Without      |
| Current (mA)   | 700             | Insulation class | II           |
| Dimmable       | No              |                  |              |
| Driver         | Remote included |                  |              |


### Physical

|                    |        |
|--------------------|--------|
| Color              | Copper |
| Orientation        | Fixed  |
| Weight (kg)        | 0.99   |
| Spot diameter (mm) | 145    |
| Lifespan (L70 B10) | L80B50 |

### Note

Pre-installation frame. To be ordered separately.

Kap Ø 145 Deep



---

Installation Frame Trim  
08.8491.GL

---

Installation Frame No Trim  
08.8156.00

---

Installation Frame Trim  
08.8491.BU



---

Installation Frame Trim  
08.8491.14

---

Installation Frame Trim  
08.8491.30