

*NO TRIM
**TRIM



Kap Ø 145 Deep

■ 03.4587.74 - Black


Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	615
Power (W)	17W	Mountings	Ceiling recessed
System power (W)	17	Environment	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	38
Beam angle C90-270 (°)	38
UGRL	3
Efficiency (lm/W)	36



Beam Angle: 38°

h(m)	E(lx)	D(m)
1	1698	0.69
2	424	1.38
3	189	2.07
4	106	2.76
5	68	3.45

Luminous flux luminaire
615 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Driver type	Non Dimmable
Voltage (V)	27	Emergency	Without
Current (mA)	600	Insulation class	II
Dimmable	No		
Driver	Remote included		


Physical

Color	Black
Orientation	Fixed
Weight (kg)	0.88
Spot diameter (mm)	145
Lifespan (L70 B10)	L80B50

Note

Pre-installation frame. To be ordered separately.

Kap Ø 145 Deep



Installation Frame Trim
08.8491.BU

Installation Frame No Trim
08.8156.00

Installation Frame Trim
08.8491.GL



Installation Frame Trim
08.8491.30

Installation Frame Trim
08.8491.14