


\*NO TRIM  
\*\*TRIM



## Kap Ø 145 Deep Dali

■ 03.4586.BU.DA - Blue


Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.

### Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 600                 |
| Power (W)        | 17W   | Mountings      | Ceiling recessed    |
| System power (W) | 17    | Environment    | Indoor dry location |
| CCT (K)          | 3000K |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 42        |
| Beam angle C90-270 (°) | 42        |
| UGRL                   | 3         |
| Efficiency (lm/W)      | 35        |



Beam Angle: 42°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 1351  | 0.77 |
| 2    | 338   | 1.53 |
| 3    | 150   | 2.30 |
| 4    | 84    | 3.07 |
| 5    | 54    | 3.83 |

Luminous flux luminaire  
600 lm (EXTREME CUT OFF)

### Electrical

|                |                 |                  |                 |
|----------------|-----------------|------------------|-----------------|
| Frequency (Hz) | 50/60           | Driver type      | Dimmable DALI 1 |
| Voltage (V)    | 27              | Emergency        | Without         |
| Current (mA)   | 600             | Insulation class | II              |
| Dimmable       | Yes             |                  |                 |
| Driver         | Remote included |                  |                 |

### Physical

|                    |        |
|--------------------|--------|
| Color              | Blue   |
| Orientation        | Fixed  |
| Weight (kg)        | 0.88   |
| Spot diameter (mm) | 145    |
| Lifespan (L70 B10) | L80B50 |

### Note

Pre-installation frame. To be ordered separately.

Kap Ø 145 Deep Dali




Installation Frame Trim  
08.8491.14



Installation Frame Trim  
08.8491.BU



Installation Frame Trim  
08.8491.30



Installation Frame No Trim  
08.8156.00



Installation Frame Trim  
08.8491.GL