


03.4588.74 - Black

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.




*NO TRIM
**TRIM



Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1047
Power (W)	17W	Mountings	Ceiling recessed
System power (W)	17	Environment	Indoor dry location
CCT (K)	3000K		

Lighting type	Indirect, Direct
LED type	LED array
Light distribution	Asymmetric
Optical type	Wall Washer Down
Beam angle (°)	55
Beam angle C90-270 (°)	63
UGRL	18
Efficiency (lm/W)	61



Luminous flux luminaire
1047 lm (EXTREME CUT OFF)

Beam Angle: 55°

h(m)	E(lx)	D(m)
1	1066	1.14
2	267	2.29
3	118	3.43
4	67	4.57
5	43	5.72

Frequency (Hz)	50/60	Driver type	Non Dimmable
Voltage (V)	27	Emergency	Without
Current (mA)	600	Insulation class	II
Dimmable	No		
Driver	Remote included		

Color	Black
Orientation	Fixed
Weight (kg)	0.94
Spot diameter (mm)	145
Lifespan (L70 B10)	L80B50

Pre-installation frame. To be ordered separately.

Kap Ø 145 Wall-Washer



Installation Frame Trim
08.8491.BU




Installation Frame Trim
08.8491.GL



Installation Frame Trim
08.8491.14



Installation Frame Trim
08.8491.30



Installation Frame No Trim
08.8251.00