



## Kap Ø 145 Wall-Washer

■ 03.4589.CU - Copper

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.



\*NO TRIM  
\*\*TRIM




### Main specifications

Number of heads	1	Net lumen (lm)	1117
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	17W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

### Optical

Lighting type	Indirect, Direct
LED type	LED array
Light distribution	Asymmetric
Optical type	Wall Washer
	Down
Beam angle (°)	58
Beam angle C90-270 (°)	67
Efficiency (lm/W)	65



Beam Angle:	58°		
	h(m)	E(lx)	D(m)
1	1083	1.09	
2	271	2.18	
3	120	3.27	
4	68	4.36	
5	43	5.45	

Luminous flux luminaire  
1117 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	27.40	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

### Physical

Color	Copper
Orientation	Fixed
Weight (kg)	0.94
Spot diameter (mm)	145

### Note

Pre-installation frame. To be ordered separately.

## Kap Ø 145 Wall-Washer



---

Installation Frame Trim  
08.8491.GL




---

Installation Frame Trim  
08.8491.14



---

Installation Frame Trim  
08.8491.30



---

Installation Frame No Trim  
08.8251.00



---

Installation Frame Trim  
08.8491.BU