


Kap Ø 145 Wall-Washer 1-10V

■ 03.4588.GL.1V - Gold

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.



*NO TRIM
**TRIM




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 1185 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 17W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|------------------|
| Lighting type | Indirect, Direct |
| LED type | LED array |
| Light distribution | Asymmetric |
| Optical type | Wall Washer |
| | Down |
| Beam angle (°) | 55 |
| Beam angle C90-270 (°) | 59 |
| Efficiency (lm/W) | 69 |



| Beam Angle: 54° | | |
|-----------------|-------|------|
| h(m) | E(lx) | D(m) |
| 1 | 1253 | 1.13 |
| 2 | 313 | 2.26 |
| 3 | 139 | 3.39 |
| 4 | 78 | 4.52 |
| 5 | 50 | 5.65 |

Luminous flux luminaire
1185 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|-----------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 27.40 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable 1-10V | | |


Physical

| | |
|---------------------------|-------|
| Color | Gold |
| Orientation | Fixed |
| Weight (kg) | 0.94 |
| Spot diameter (mm) | 145 |

Note

Pre-installation frame. To be ordered separately.

Kap Ø 145 Wall-Washer 1-10V



Installation Frame No Trim
08.8251.00



Installation Frame Trim
08.8491.14



Installation Frame Trim
08.8491.BU



Installation Frame Trim
08.8491.GL



Installation Frame Trim
08.8491.30