



Kap Ø 145 Wall-Washer Dali

■ 03.4498.74BDA - Black

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.



*NO TRIM
**TRIM




Main specifications

Number of heads	1	CRI	98
Lamp category	LED	Net lumen (lm)	747
Power (W)	17W	Mountings	Ceiling recessed
System power (W)	17	Environment	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Indirect, Direct
LED type	Phosphor LED
Light distribution	Asymmetric
Optical type	Wall Washer
Beam angle (°)	Down
Beam angle C90-270 (°)	57
UGRL	64
Efficiency (lm/W)	17
	43



Beam Angle: 57°

h(m)	E(lx)	D(m)
1	713	1.24
2	178	2.48
3	79	3.72
4	45	4.96
5	29	6.20

Luminous flux luminaire
747 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Driver type	Dimmable DALI 1
Voltage (V)	22	Emergency	Without
Current (mA)	700	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	0.94
Spot diameter (mm)	145
Lifespan (L70 B10)	L80B50

Note

Pre-installation frame. To be ordered separately.

Kap Ø 145 Wall-Washer Dali



Installation Frame Trim
08.8491.14




Installation Frame Trim
08.8491.30



Installation Frame Trim
08.8491.GL



Installation Frame Trim
08.8491.BU



Installation Frame No Trim
08.8251.00