


## Kap Ø 50 Adjustable Optic Medium

05.7311.B1 - White

Recessed luminaire with LED light source. Power supply not included. Remote power supply to be installed in an accessible place.




### Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 488                 |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Ceiling recessed    |
| <b>Power (W)</b>       | 7.5W  | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 2700K |                       |                     |
| <b>CRI</b>             | 90    |                       |                     |

### Optical

|                               |           |
|-------------------------------|-----------|
| <b>Lighting type</b>          | Direct    |
| <b>LED type</b>               | LED array |
| <b>Light distribution</b>     | Symmetric |
| <b>Optical type</b>           | Medium    |
| <b>Beam angle (°)</b>         | 24        |
| <b>Beam angle C90-270 (°)</b> | 24        |
| <b>Efficiency (lm/W)</b>      | 56        |



|                    |              |             |  |
|--------------------|--------------|-------------|--|
| <b>Beam Angle:</b> | 24°          |             |  |
| <b>h(m)</b>        | <b>E(lx)</b> | <b>D(m)</b> |  |
| 1                  | 2032         | 0.43        |  |
| 2                  | 508          | 0.86        |  |
| 3                  | 226          | 1.30        |  |
| 4                  | 127          | 1.73        |  |
| 5                  | 81           | 2.16        |  |

Luminous flux luminaire  
488 lm (EXTREME CUT OFF)

### Electrical

|                     |   |                         |         |
|---------------------|---|-------------------------|---------|
| <b>Voltage (V)</b>  | 35  | <b>Emergency</b>        | Without |
| <b>Current (mA)</b> | 200   | <b>Insulation class</b> | III     |
| <b>Dimmable</b>     | Yes   |                         |         |
| <b>Driver</b>       | Remote excluded   |                         |         |
| <b>Driver type</b>  | Non Dimmable, Dimmable DALI 2, Dimmable 0-10V, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming |                         |         |

### Physical

|                            |            |                           |     |
|----------------------------|------------|---------------------------|-----|
| <b>Color</b>               | White      | <b>Rotation (°)</b>       | 360 |
| <b>Orientation</b>         | Adjustable | <b>Spot diameter (mm)</b> | 54  |
| <b>Recessed depth (mm)</b> | 100        |                           |     |
| <b>Weight (kg)</b>         | 0,162      |                           |     |
| <b>Tilt (°)</b>            | 20         |                           |     |

### Note

Pre-installation frame. To be ordered separately.


## Kap Ø 50 Adjustable Optic Medium



Continuous current power supply.  
220/240V – 50/60Hz. Adjustable Current  
150 mA – 7,2W / 200 mA – 9,5W / 250 mA  
– 12W / 300 mA – 14,5W / 350 mA  
– 17W / 400 mA – 19,5W / 450 mA – 21,5W  
/ 500 mA – 24W. Mains or push dimming  
60.9421

Non dimmable continuous current  
power supply of 220/240V – 50/60Hz  
with power current selected through  
adjustable with switch 200 mA – 8,5W /  
300 mA – 13W / 350 mA – 15W / 400 mA  
– 17,5W / 450 mA – 19,5W / 500 mA –  
22W  
60.9160

Continuous current power supply,  
dimmable DALI 2, 220/240V – 50/60Hz,  
200mA – 20W  
60.9604



Casambi Controller 220-240V. Remote  
Installation  
60.9392

Installation frame No Trim  
08.9114.00

Continuous current power supply, 0-  
10V dimmable, 220/240V – 50/60Hz,  
200mA – 20W  
60.9483