




## Kap Ø 50 Fixed Optic Flood

■ 05.7302.GL - Gold

Recessed luminaire with LED light source. Power supply not included. Remote power supply to be installed in an accessible place.




## Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 476                 |
| Power (W)        | 7,3W  | Mountings      | Ceiling recessed    |
| System power (W) | 8.6   | Environment    | Indoor dry location |
| CCT (K)          | 2700K |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 49        |
| Beam angle C90-270 (°) | 49        |
| UGRL                   | 15        |
| Efficiency (lm/W)      | 55        |



Beam Angle: 49°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 733   | 0.90 |
| 2    | 183   | 1.81 |
| 3    | 81    | 2.71 |
| 4    | 46    | 3.61 |
| 5    | 29    | 4.52 |

Luminous flux luminaire  
476 lm (EXTREME CUT OFF)

## Electrical

|              |                                                                                                                     |                  |         |
|--------------|---------------------------------------------------------------------------------------------------------------------|------------------|---------|
| Voltage (V)  | 35                                                                                                                  | Emergency        | Without |
| Current (mA) | 200                                                                                                                 | Insulation class | III     |
| Dimmable     | Yes                                                                                                                 |                  |         |
| Driver       | Remote excluded                                                                                                     |                  |         |
| Driver type  | Non Dimmable, Dimmable DALI 2, Dimmable 0-10V, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming |                  |         |


## Physical

|                     |       |                    |        |
|---------------------|-------|--------------------|--------|
| Color               | Gold  | Lifespan (L70 B10) | L80B50 |
| Orientation         | Fixed |                    |        |
| Recessed depth (mm) | 100   |                    |        |
| Weight (kg)         | 0.14  |                    |        |
| Spot diameter (mm)  | 54    |                    |        |

## Note

Pre-installation frame. To be ordered separately.

## Kap Ø 50 Fixed Optic Flood



Casambi Controller 220-240V. Remote Installation  
60.9392



Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200 mA – 8,5W / 300 mA – 13W / 350 mA – 15W / 400 mA – 17,5W / 450 mA – 19,5W / 500 mA – 22W  
60.9160



Installation frame No Trim  
08.9114.00



Continuous current power supply. 220/240V – 50/60Hz. Adjustable Current 150 mA – 7,2W / 200 mA – 9,5W / 250 mA – 12W / 300 mA -14,5W / 350 mA -17W/400 mA – 19,5W / 450 mA -21,5W / 500 mA – 24W. Mains or push dimming  
60.9421



Continuous current power supply, 0-10V dimmable, 220/240V – 50/60Hz, 200mA – 20W  
60.9483



Continuous current power supply, dimmable DALI 2, 220/240V – 50/60Hz, 200mA – 20W  
60.9604