



Kap Ø 50 Fixed Optic Spot

■ 05.7305.BU - Blue

Recessed luminaire with LED light source. Power supply not included. Remote power supply to be installed in an accessible place.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 565 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 7.5W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 15 |
| Beam angle C90-270 (°) | 15 |
| Efficiency (lm/W) | 65 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 15° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 5744 | 0.26 | |
| 2 | 1436 | 0.52 | |
| 3 | 638 | 0.78 | |
| 4 | 359 | 1.04 | |
| 5 | 230 | 1.30 | |

Luminous flux luminaire
565 lm (EXTREME CUT OFF)

Electrical

| | | | |
|---------------------|---|-------------------------|---------|
| Voltage (V) | 35 | Emergency | Without |
| Current (mA) | 200 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Non Dimmable, Dimmable DALI 2, Dimmable 0-10V, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming | | |

Physical

| | |
|----------------------------|-------|
| Color | Blue |
| Orientation | Fixed |
| Recessed depth (mm) | 100 |
| Weight (kg) | 0,136 |
| Spot diameter (mm) | 54 |

Note

Pre-installation frame. To be ordered separately.

Kap Ø 50 Fixed Optic Spot



Installation frame No Trim
08.9114.00



Continuous current power supply,
dimmable DALI 2, 220/240V – 50/60Hz,
200mA – 20W
60.9604



Casambi Controller 220-240V. Remote
Installation
60.9392



Non dimmable continuous current
power supply of 220/240V – 50/60Hz
with power current selected through
adjustable with switch 200 mA – 8,5W /
300 mA – 13W / 350 mA – 15W / 400 mA
– 17,5W / 450 mA – 19,5W / 500 mA –
22W
60.9160



Continuous current power supply, 0-
10V dimmable, 220/240V – 50/60Hz,
200mA – 20W
60.9483



Continuous current power supply.
220/240V – 50/60Hz. Adjustable Current
150 mA – 7,2W / 200 mA – 9,5W / 250 mA
– 12W / 300 mA -14,5W / 350 mA
-17W/400 mA – 19,5W /450 mA -21,5W
/500 mA – 24W. Mains or push dimming
60.9421