


### Kap Ø 80 Adjustable

■ 03.4237.74 - Black

Recessed luminaire with main voltage source.



#### Main specifications

|                  |                  |             |                     |
|------------------|------------------|-------------|---------------------|
| Number of heads  | 1                | Environment | Indoor dry location |
| Lamp category    | LED retrofit     |             |                     |
| Power (W)        | MAX 8W           |             |                     |
| System power (W) | 8                |             |                     |
| Mountings        | Ceiling recessed |             |                     |

#### Optical

|                    |           |
|--------------------|-----------|
| Lighting type      | Direct    |
| Lamp type          | PAR16     |
| Light distribution | Symmetric |

#### Electrical


|                |         |                  |    |
|----------------|---------|------------------|----|
| Frequency (Hz) | 50/60   | Insulation class | II |
| Voltage (V)    | 230     |                  |    |
| Current (mA)   | -9      |                  |    |
| Lamp holder    | GZ10    |                  |    |
| Emergency      | Without |                  |    |

#### Physical

|                     |            |                    |     |
|---------------------|------------|--------------------|-----|
| Color               | Black      | Rotation (°)       | 360 |
| Orientation         | Adjustable | Spot diameter (mm) | 74  |
| Recessed depth (mm) | 155        |                    |     |
| Weight (kg)         | 0.12       |                    |     |
| Tilt (°)            | 20         |                    |     |

#### Note

Not suitable for lens accessories.



## Kap Ø 80 Adjustable



---

Installation frame No Trim  
08.9102.00