


03.4540.CU.LE - Copper


Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.



Number of heads	1
Lamp category	LED
Power (W)	13W
System power (W)	13
CCT (K)	2850K-1800K

CRI	95
Net lumen (lm)	663
Mountings	Ceiling recessed
Environment	Indoor dry location

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	27
Beam angle C90-270 (°)	46
UGRL	13
Efficiency (lm/W)	51



$h(m)$	$E(x)$	$D(m)$
0	0	0
1	1	1
2	2	2
3	3	3
4	4	4
5	5	5
6	6	6
7	7	7
8	8	8
9	9	9
10	10	10
11	11	11
12	12	12
13	13	13
14	14	14
15	15	15
16	16	16
17	17	17
18	18	18
19	19	19
20	20	20
21	21	21
22	22	22
23	23	23
24	24	24
25	25	25
26	26	26
27	27	27
28	28	28
29	29	29
30	30	30
31	31	31
32	32	32
33	33	33
34	34	34
35	35	35
36	36	36
37	37	37
38	38	38
39	39	39
40	40	40
41	41	41
42	42	42
43	43	43
44	44	44
45	45	45
46	46	46
47	47	47
48	48	48
49	49	49
50	50	50
51	51	51
52	52	52
53	53	53
54	54	54
55	55	55
56	56	56
57	57	57
58	58	58
59	59	59
60	60	60
61	61	61
62	62	62
63	63	63
64	64	64
65	65	65
66	66	66
67	67	67
68	68	68
69	69	69
70	70	70
71	71	71
72	72	72
73	73	73
74	74	74
75	75	75
76	76	76
77	77	77
78	78	78
79	79	79
80	80	80
81	81	81
82	82	82
83	83	83
84	84	84
85	85	85
86	86	86
87	87	87
88	88	88
89	89	89
90	90	90
91	91	91
92	92	92
93	93	93
94	94	94
95	95	95
96	96	96
97	97	97
98	98	98
99	99	99
100	100	100

1	1673	0.49
2	418	0.97
3	186	1.46
4	105	1.94
5	67	2.43

Luminous flux lumineuse
663 lm (EXTREME CUT OFF)

Frequency (Hz)	50/60
Voltage (V)	33
Current (mA)	300
Dimmable	Yes
Driver	Remote included

Driver type	Dimmable 1-10V
Emergency	Without
Insulation class	II

Color	Copper
Orientation	Adjustable
Recessed depth (mm)	91
Weight (kg)	0.24
Tilt (°)	20

Rotation (°)	360
Spot diameter (mm)	74
Lifespan (L70 B10)	L80B50

For 110V PSU versions, please consult with the front office. Diffusing lens included.

Kap Ø 80 Adjustable Optic Flood - Dim-To-Warm



Installation frame No Trim
08.9102.00