


Kap Ø 80 Adjustable Optic Medium - Dim-To-Warm

■ 03.4184.74.LE - Black

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




Main specifications

Number of heads	1	CRI	95
Lamp category	LED	Net lumen (lm)	631
Power (W)	13W	Mountings	Ceiling recessed
System power (W)	13	Environment	Indoor dry location
CCT (K)	2850K-1800K		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	28
Beam angle C90-270 (°)	28
UGRL	10
Efficiency (lm/W)	48



Beam Angle: 28°

	h(m)	E(lx)	D(m)
1	1818	0.49	
2	455	0.99	
3	202	1.48	
4	114	1.97	
5	73	2.46	

Luminous flux luminaire
631 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Driver type	Dimmable 1-10V
Voltage (V)	33	Emergency	Without
Current (mA)	300	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

Physical

Color	Black	Rotation (°)	360
Orientation	Adjustable	Spot diameter (mm)	74
Recessed depth (mm)	91	Lifespan (L70 B10)	L80B50
Weight (kg)	0.24		
Tilt (°)	20		

Note

For 110V PSU versions, please consult with the front office. Diffusing lens included.



Kap Ø 80 Adjustable Optic Medium - Dim-To-Warm



Installation frame No Trim
08.9102.00