


## Kap Ø 80 Adjustable Optic Medium - Dim-To-Warm

03.4184.CU.LE - Copper

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




## Main specifications

<b>Number of heads</b>	1	<b>CRI</b>	95
<b>Lamp category</b>	LED	<b>Net lumen (lm)</b>	683
<b>Power (W)</b>	13W	<b>Mountings</b>	Ceiling recessed
<b>System power (W)</b>	13	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2850K-1800K		

## Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22
UGRL	10
Efficiency (lm/W)	52



Beam Angle:	22°		
h(m)	E(lx)	D(m)	
1	2523	0.39	
2	631	0.78	
3	280	1.17	
4	158	1.56	
5	101	1.95	

Luminous flux lumineuse  
683 lm (EXTREME CUT OFF)

## Electrical

Frequency (Hz)	50/60	Driver type	Dimmable 1-10V
Voltage (V)	33	Emergency	Without
Current (mA)	300	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

## Physical

<b>Color</b>	Copper	<b>Rotation (°)</b>	360
<b>Orientation</b>	Adjustable	<b>Spot diameter (mm)</b>	74
<b>Recessed depth (mm)</b>	91	<b>Lifespan (L70 B10)</b>	L80B50
<b>Weight (kg)</b>	0.24		
<b>Tilt (°)</b>	20		

### Note

For 110V PSU versions, please consult with the front office. Diffusing lens included.

## Kap Ø 80 Adjustable Optic Medium - Dim-To-Warm



---

Installation frame No Trim  
08.9102.00