


03.4538.CU.LE - Copper


Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.



Number of heads	1
Lamp category	LED
Power (W)	13W
System power (W)	13
CCT (K)	2850K-1800K

CRI	95
Net lumen (lm)	680
Mountings	Ceiling recessed
Environment	Indoor dry location

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	17
Beam angle C90-270 (°)	21
UGRL	11
Efficiency (lm/W)	52


$$h(m) \quad E(lx) \quad D(m)$$

1	3385	0.30
2	846	0.60
3	376	0.90
4	212	1.20
5	135	1.50

Luminous flux lumineuse
680 lm (EXTREME CUT OFF)

Frequency (Hz)	50/60
Voltage (V)	33
Current (mA)	300
Dimmable	Yes
Driver	Remote included

Driver type	Dimmable 1-10V
Emergency	Without
Insulation class	II

Color	Copper
Orientation	Adjustable
Recessed depth (mm)	91
Weight (kg)	0.24
Tilt (°)	20

Rotation (°)	360
Spot diameter (mm)	74
Lifespan (L70 B10)	L80B50

For 110V PSU versions, please consult with the front office. Diffusing lens included.

Kap Ø 80 Adjustable Optic Spot - Dim-To-Warm



Installation frame No Trim
08.9102.00