



## 03.4532.GL - Gold

Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.



|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 687                 |
| Power (W)        | 9.2W  | Mountings      | Ceiling recessed    |
| System power (W) | 9.2   | Environment    | Indoor dry location |
| CCT (K)          | 3000K |                |                     |

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 45        |
| Beam angle C90-270 (°) | 45        |
| UGRL                   | 14        |
| Efficiency (lm/W)      | 74        |



Luminous flux lumineuse  
687 lm (EXTREME CUT OFF)

Beam Angle: 45°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 1255  | 0.83 |
| 2    | 314   | 1.66 |
| 3    | 139   | 2.48 |
| 4    | 78    | 3.31 |
| 5    | 50    | 4.14 |

|                     |                                                                                                                                               |                         |         |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|---------|
| <b>Voltage (V)</b>  | 18                                                                                                                                            | <b>Emergency</b>        | Without |
| <b>Current (mA)</b> | 500                                                                                                                                           | <b>Insulation class</b> | III     |
| <b>Dimmable</b>     | Yes                                                                                                                                           |                         |         |
| <b>Driver</b>       | Remote<br>excluded                                                                                                                            |                         |         |
| <b>Driver type</b>  | Non Dimmable,<br>Dimmable DALI<br>2, Dimmable 0-<br>10V, Dimmable<br>Casambi,<br>Dimmable 1-<br>10V, Dimmable<br>DALI 1, Mains<br>Cut Dimming |                         |         |

|                     |       |                                  |
|---------------------|-------|----------------------------------|
| Color               | Gold  | <b>Lifespan (L70 B10)</b> L80B50 |
| Orientation         | Fixed |                                  |
| Recessed depth (mm) | 91    |                                  |
| Weight (kg)         | 0.24  |                                  |
| Spot diameter (mm)  | 74    |                                  |

Diffusing lens included.

## Kap Ø 80 Fixed Optic Flood



Continuous current power supply of 12-20W, 110/240V – 50/60Hz with power current selected through adjustable 350mA – 17W / 400mA – 19W / 450 / 550 / 600 / 700mA – 20W regulable Dali 1 y Dali 2  
60.9222

Continuous current power supply, 1-10V, regulable Mains, leading & trailing edge 220/240V – 50/60Hz, 500mA – 10W  
60.9411

Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/ 650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming  
60.9188



Installation frame No Trim  
08.9102.00

Continuous current power supply of 10-20W, 110/240V – 50/60Hz with power current selected through adjustable 250 mA – 10W / 350 mA – 15W / 400 mA – 17W / 450 mA – 19W / 500/550/600/700 mA – 20W, Dali 1 switch.  
60.8847

Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W  
60.9207



---

Non dimmable continuous current  
power supply of 220/240V – 50/60Hz  
with power current selected through  
adjustable with switch 200 mA – 8,5W /  
300 mA – 13W / 350 mA – 15W / 400 mA  
– 17,5W / 450 mA – 19,5W / 500 mA –  
22W  
60.9160