


## Kap Ø 80 Fixed Optic Flood - Dim-To-Warm

■ 03.4532.GL.LE - Gold

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




### Main specifications

Number of heads	1	CRI	95
Lamp category	LED	Net lumen (lm)	690
Power (W)	13W	Mountings	Ceiling recessed
System power (W)	13	Environment	Indoor dry location
CCT (K)	2850K-1800K		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	47
Beam angle C90-270 (°)	45
UGRL	14
Efficiency (lm/W)	53



Beam Angle: 47°

	h(m)	E(lx)	D(m)
1	1183	0.87	
2	296	1.75	
3	131	2.62	
4	74	3.50	
5	47	4.37	

Luminous flux luminaire  
690 lm (EXTREME CUT OFF)

### Electrical


Frequency (Hz)	50/60	Driver type	Dimmable 1-10V
Voltage (V)	33	Emergency	Without
Current (mA)	300	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

### Physical

Color	Gold	Lifespan (L70 B10)	L80B50
Orientation	Fixed		
Recessed depth (mm)	91		
Weight (kg)	0.24		
Spot diameter (mm)	74		

### Note

For 110V PSU versions, please consult with the front office. Diffusing lens included.



## Kap Ø 80 Fixed Optic Flood - Dim-To-Warm



---

Installation frame No Trim  
08.9102.00