


Kap Ø 80 Fixed Optic Medium - Dim-To-Warm

■ 03.4180.BU.LE - Blue

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




Main specifications

Number of heads	1	CRI	95
Lamp category	LED	Net lumen (lm)	641
Power (W)	13W	Mountings	Ceiling recessed
System power (W)	13	Environment	Indoor dry location
CCT (K)	2850K-1800K		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	27
Beam angle C90-270 (°)	27
UGRL	11
Efficiency (lm/W)	49



Beam Angle: 27°

	h(m)	E(lx)	D(m)
1	1876	0.48	
2	469	0.96	
3	208	1.44	
4	117	1.92	
5	75	2.40	

Luminous flux luminaire
641 lm (EXTREME CUT OFF)

Electrical


Frequency (Hz)	50/60	Driver type	Dimmable 1-10V
Voltage (V)	33	Emergency	Without
Current (mA)	300	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

Physical

Color	Blue	Lifespan (L70 B10)	L80B50
Orientation	Fixed		
Recessed depth (mm)	91		
Weight (kg)	0.24		
Spot diameter (mm)	74		

Note

For 110V PSU versions, please consult with the front office. Diffusing lens included.



Kap Ø 80 Fixed Optic Medium - Dim-To-Warm



Installation frame No Trim
08.9102.00