


Kap Ø 80 Fixed Optic Spot - Dim-To-Warm

03.4530.B1.LE - White

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	740
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	13W	Environment	Indoor dry location
CCT (K)	2850K-1800K		
CRI	95		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	20
Beam angle C90-270 (°)	19
Efficiency (lm/W)	56



Beam Angle:	20°		
h(m)	E(lx)	D(m)	
1	2805	0.35	
2	701	0.69	
3	312	1.04	
4	175	1.39	
5	112	1.74	

Luminous flux luminaire
740 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Driver type	Dimmable 1-10V
Voltage (V)	33.00	Emergency	Without
Current (mA)	300	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

Physical

Color	White
Orientation	Fixed
Recessed depth (mm)	91
Weight (kg)	0.24
Spot diameter (mm)	74

Note

For 110V PSU versions, please consult with the front office. Diffusing lens included.



Kap Ø 80 Fixed Optic Spot - Dim-To-Warm



Installation frame No Trim
08.9102.00