


## Update

05.7460.B1 - White


Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.



|                  |       |
|------------------|-------|
| Number of heads  | 1     |
| Lamp category    | LED   |
| Power (W)        | 13W   |
| System power (W) | 13.4  |
| CCT (K)          | 3000K |

|                       |                     |
|-----------------------|---------------------|
| <b>CRI</b>            | 90                  |
| <b>Net lumen (lm)</b> | 1045                |
| <b>Mountings</b>      | Ceiling recessed    |
| <b>Environment</b>    | Indoor dry location |

|                        |           |
|------------------------|-----------|
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 50        |
| Beam angle C90-270 (°) | 50        |
| UGRL                   | 20        |
| Efficiency (lm/W)      | 77        |



Beam Angle: 50°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 1615  | 0.94 |
| 2    | 404   | 1.89 |
| 3    | 179   | 2.83 |
| 4    | 101   | 3.77 |
| 5    | 65    | 4.71 |

Luminous flux lumineuse  
1045 lm (EXTREME CUT OFF)

|                     |                                                                                                                                               |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Voltage (V)</b>  | 18                                                                                                                                            |
| <b>Current (mA)</b> | 700                                                                                                                                           |
| <b>Dimmable</b>     | Yes                                                                                                                                           |
| <b>Driver</b>       | Remote<br>excluded                                                                                                                            |
| <b>Driver type</b>  | Non Dimmable,<br>Dimmable DALI<br>2, Dimmable 0-<br>10V, Dimmable<br>Casambi,<br>Dimmable 1-<br>10V, Dimmable<br>DALI 1, Mains<br>Cut Dimming |

|                               |                |
|-------------------------------|----------------|
| Emergency<br>Insulation class | Without<br>III |
|-------------------------------|----------------|

|                     |            |
|---------------------|------------|
| Color               | White      |
| Orientation         | Adjustable |
| Recessed depth (mm) | 150        |
| Weight (kg)         | 0.24       |
| Tilt (°)            | 20         |

|                    |        |
|--------------------|--------|
| Rotation (°)       | 360    |
| Spot diameter (mm) | 74     |
| Lifespan (L70 B10) | L80B50 |

## Kap Ø 80 Plus Adjustable Optic Flood



Continuous current power supply of 12-20W, 110/240V – 50/60Hz with power current selected through adjustable 350mA – 17W / 400mA – 19W / 450 / 550 / 600 / 700mA – 20W regulable Dali 1 y Dali 2  
60.9222



Continuous current power supply, Mains dimming, leading & trailing edge 220/240V – 50/60Hz, 300mA-14W / 350mA-17W / 400mA-19W / 450/500/600/650/700/750/800/900mA – 20W  
60.9467



Continuous current power supply of 10-20W, 110/240V – 50/60Hz with power current selected through adjustable 250 mA – 10W / 350 mA – 15W / 400 mA – 17W / 450 mA – 19W / 500/550/600/700 mA – 20W, Dali 1 switch.  
60.8847



Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch. 350mA – 15W / 400mA – 17W / 450mA – 19W / 500mA – 22W / 550mA – 24W / 600mA – 26W / 650mA – 28W / 700mA – 30W no regulable  
60.9592



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W  
60.9207



Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming  
60.9188



---

Installation frame No Trim  
08.9102.00