

## Kap Ø105 Deep

■ 05.7151.BU - Blue

Recessed luminaire with LED light source. Remote electronic transformer 220/240V not included. Pre-installation frame. To be ordered separately.


Recessed luminaire with LED light source. Remote electronic transformer 220/240V not included. Pre-installation frame. To be ordered separately.

### Main specifications

|                  |       |                |                  |
|------------------|-------|----------------|------------------|
| Number of heads  | 1     | CRI            | 90               |
| Lamp category    | LED   | Net lumen (lm) | 1307             |
| Power (W)        | 23W   | Mountings      | Ceiling recessed |
| System power (W) | 25.9  | Environment    | Indoor           |
| CCT (K)          | 2700K |                |                  |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 25        |
| Beam angle C90-270 (°) | 25        |
| Efficiency (lm/W)      | 27        |



Beam Angle: 25°

|   | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 6863 | 0.45  |      |
| 2 | 1716 | 0.90  |      |
| 3 | 763  | 1.35  |      |
| 4 | 429  | 1.79  |      |
| 5 | 275  | 2.24  |      |

Luminous flux luminaire  
1307 lm (EXTREME CUT OFF)


### Electrical

|              |                                                                                            |                  |         |
|--------------|--------------------------------------------------------------------------------------------|------------------|---------|
| Voltage (V)  | 34                                                                                         | Emergency        | Without |
| Current (mA) | 650                                                                                        | Insulation class | III     |
| Dimmable     | Yes                                                                                        |                  |         |
| Driver       | Remote                                                                                     |                  |         |
| Driver type  | Electronic,<br>Electronic dimmable,<br>Electronic dimmable 1-10V, Electronic dimmable DALI |                  |         |

### Physical

|                     |       |
|---------------------|-------|
| Color               | Blue  |
| Orientation         | Fixed |
| Recessed depth (mm) | 190   |
| Weight (kg)         | 0,48  |
| Spot diameter (mm)  | 106   |

## Kap Ø105 Deep



Installation frame No Trim  
08.9104.00



Installation can for concrete  
08.8420.00



Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power currentselected through adjustableswitch. 350mA – 15W / 400mA – 17W / 450mA – 19W / 500mA – 22W / 550mA – 24W / 600mA – 26W / 650mA – 28W / 700mA – 30W no regulable  
60.9592



Continuous current power supply, 0/1-10V dimmable, 220/240V – 50/60Hz, 36W – 700 mA  
60.9439



Continuous current supply source of 240V – 50/60Hz with dimmable DALI 2  
60.9186



Continuous current power supply, dimmable Casambi, 220/240V – 50/60Hz, 35W – 650mA / 36W – 700 mA.  
60.9207