

## Kap Ø105 Deep

■ 05.7156.BU - Blue

Recessed luminaire with LED light source. Remote electronic transformer 220/240V not included. Pre-installation frame. To be ordered separately.


Recessed luminaire with LED light source. Remote electronic transformer 220/240V not included. Pre-installation frame. To be ordered separately.

### Main specifications

<b>Number of heads</b>	1	<b>CRI</b>	90
<b>Lamp category</b>	LED	<b>Net lumen (lm)</b>	703
<b>Power (W)</b>	23W	<b>Mountings</b>	Ceiling recessed
<b>System power (W)</b>	25.9	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	25
<b>Beam angle C90-270 (°)</b>	25



Beam Angle: 25°

h(m)	E(lx)	D(m)
1	7765	0.45
2	1941	0.89
3	863	1.34
4	485	1.79
5	311	2.23

Luminous flux luminaire  
1475 lm (EXTREME CUT OFF)

### Electrical

<b>Voltage (V)</b>	34	<b>Emergency</b>	Without
<b>Current (mA)</b>	650	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		

### Certification / Marking



### Physical

<b>Color</b>	Blue	<b>Length (mm)</b>	106
<b>Orientation</b>	Fixed		
<b>Recessed depth (mm)</b>	190		
<b>Weight (kg)</b>	0,48		
<b>Spot diameter (mm)</b>	106		

## Kap Ø105 Deep



---

Installation frame No Trim  
08.9104.00



---

Installation can for concrete  
08.8420.00



---

Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch.  
60.9592



---

Continuous current power supply of 13-20W, 110\*/240V – 50/60Hz with power current selected through adjustable switch. Synchronisation cables not included.  
60.9188



---

Constant Current Power Supply for LED. Dimmable DALI. 10-20W  
60.8847



---

Power supply Casambi. 21.5W-32W  
60.9207