



# Kap Ø105 Fixed Optic Medium

05.7106.B1 - White


Recessed luminaire with LED light source. Remote transformer not included. Pre-installation frame. To be ordered separately.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	2222
Power (W)	25.9W	Mountings	Ceiling recessed
System power (W)	25.9	Environment	Indoor
CCT (K)	3000K		

# Optical

Light distribution Symmetric Optical type Medium Beam angle (°) 27 Beam angle C90-270 (°) 27	Lighting type	Direct
Optical type Medium Beam angle (°) 27 Beam angle C90-270 (°) 27	LED type	LED array
Beam angle (°) 27 Beam angle C90-270 (°) 27	Light distribution	Symmetric
Beam angle C90-270 (°) 27	Optical type	Medium
• • • • • • • • • • • • • • • • • • • •	Beam angle (°)	27
Efficiency (lm/W) 85	Beam angle C90-270 (°)	27
	Efficiency (lm/W)	85



Luminous flux luminaire 2222 lm (EXTREME CUT OFF)

Without

Beam Angle:		2/°
h(m)	E(lx)	D(m)
1	8281	0.48
2	2070	0.97
3	920	1.45
4	518	1.93
5	331	2.41

#### **Electrical**

Voltage (V)	34	Emergency
Current (mA)	650	Insulation class
Dimmable	Yes	
Driver	Remote	
Driver type	Electronic,	
	Electronic	
	dimmable,	
	Electronic	
	dimmable 1-	

10V, Electronic dimmable DALI

### Physical

Color	White
Orientation	Fixed
Recessed depth (mm)	150
Weight (kg)	0,48
Spot diameter (mm)	105

# Kap Ø105 Fixed Optic Medium







Installation frame No Trim 08.0132.00

Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power currentselected through adjustableswitch. 60.9592 Continuous current power supply of 13-20W, 110\*/240V – 50/60Hz with power current selected through adjustable switch. 1-10V or push dimming. 60.9188





Constant Current Power Supply for LED. Dimmable DALI. 10-20W 60.8847

Continuous current power supply, dimmable Casambi, 220/240V – 50/60Hz, 35W – 650mA / 36W – 700 mA. 60.9207