

\*NO TRIM  
\*\*TRIM

## Kap Ø145

03.4496.B1B - White


Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	775
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	17W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		
<b>CRI</b>	98		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Phosphor LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	53
<b>Beam angle C90-270 (°)</b>	53



<b>Beam Angle:</b>	53°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	928	1.00	
2	232	2.00	
3	103	3.00	
4	58	4.01	
5	37	5.01	

Luminous flux luminaire  
775 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	22.30	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.88
<b>Spot diameter (mm)</b>	145

### Certification / Marking



### Note

Pre-installation frame. To be ordered separately.

## Kap Ø145



---

Installation Frame Trim  
08.8491.BU



---

Installation Frame Trim  
08.8491.14




---

Installation Frame Trim  
08.8491.30



---

Installation can for concrete  
08.8421.00



---

Installation Frame No Trim  
08.8156.00



---

Installation Frame Trim  
08.8491.GL