


\*NO TRIM  
\*\*TRIM



## Kap Ø145

03.4584.CU - Copper


Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.

### Main specifications

|                 |       |                |                  |
|-----------------|-------|----------------|------------------|
| Number of heads | 1     | Net lumen (lm) | 1023             |
| Lamp category   | LED   | Mountings      | Ceiling recessed |
| Power (W)       | 17W   | Environment    | Indoor           |
| CCT (K)         | 3000K |                |                  |
| CRI             | 90    |                |                  |

### Optical

|                        |                 |
|------------------------|-----------------|
| Lighting type          | Direct          |
| LED type               | LED array       |
| Light distribution     | Symmetric Flood |
| Optical type           |                 |
| Beam angle (°)         | 43              |
| Beam angle C90-270 (°) | 43              |
| Efficiency (lm/W)      | 60              |



Beam Angle: 43°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2131  | 0.78 |
| 2    | 533   | 1.57 |
| 3    | 237   | 2.35 |
| 4    | 133   | 3.14 |
| 5    | 85    | 3.92 |

Luminous flux luminaire  
1023 lm (EXTREME CUT OFF)

### Electrical

|                |            |                  |         |
|----------------|------------|------------------|---------|
| Frequency (Hz) | 50/60      | Emergency        | Without |
| Voltage (V)    | 27.40      | Insulation class | II      |
| Dimmable       | No         |                  |         |
| Driver         | Remote     |                  |         |
| Driver type    | Electronic |                  |         |

### Physical

|                    |        |
|--------------------|--------|
| Color              | Copper |
| Orientation        | Fixed  |
| Weight (kg)        | 0.88   |
| Spot diameter (mm) | 145    |

### Note

Pre-installation frame. To be ordered separately.

Kap Ø145



Installation Frame Trim  
08.8491.BU




Installation Frame Trim  
08.8491.14



Installation Frame Trim  
08.8491.30



Installation can for concrete  
08.8421.00



Installation Frame No Trim  
08.8156.00



Installation Frame Trim  
08.8491.GL