

\*NO TRIM  
\*\*TRIM



## Kap Ø145 1-10V

■ 03.4585.74.1V - Black


Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.

### Main specifications

|                 |       |                |                  |
|-----------------|-------|----------------|------------------|
| Number of heads | 1     | Net lumen (lm) | 815              |
| Lamp category   | LED   | Mountings      | Ceiling recessed |
| Power (W)       | 17W   | Environment    | Indoor           |
| CCT (K)         | 2700K |                |                  |
| CRI             | 90    |                |                  |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 50        |
| Beam angle C90-270 (°) | 50        |
| Efficiency (lm/W)      | 47        |



Beam Angle: 50°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 1370  | 0.93 |
| 2    | 343   | 1.86 |
| 3    | 152   | 2.79 |
| 4    | 86    | 3.72 |
| 5    | 55    | 4.65 |

Luminous flux luminaire  
815 lm (EXTREME CUT OFF)

### Electrical

|                |                |                  |         |
|----------------|----------------|------------------|---------|
| Frequency (Hz) | 50/60          | Emergency        | Without |
| Voltage (V)    | 27.40          | Insulation class | II      |
| Dimmable       | Yes            |                  |         |
| Driver         | Remote         |                  |         |
| Driver type    | Electronic     |                  |         |
|                | dimnable 1-10V |                  |         |

### Physical

|                    |       |
|--------------------|-------|
| Color              | Black |
| Orientation        | Fixed |
| Weight (kg)        | 0.88  |
| Spot diameter (mm) | 145   |

### Note

Pre-installation frame. To be ordered separately.

Kap Ø145 1-10V



Installation Frame Trim  
08.8491.BU




Installation Frame Trim  
08.8491.14



Installation Frame Trim  
08.8491.30



Installation can for concrete  
08.8421.00



Installation Frame No Trim  
08.8156.00



Installation Frame Trim  
08.8491.GL