


\*NO TRIM  
\*\*TRIM



## Kap Ø145 Deep Dali

■ 03.4587.CU.DA - Copper


Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	842
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	17W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	24
<b>Beam angle C90-270 (°)</b>	24
<b>Efficiency (lm/W)</b>	49



Beam Angle: 24°

h(m)	E(lx)	D(m)
1	3494	0.43
2	873	0.86
3	388	1.29
4	218	1.72
5	140	2.15

Luminous flux luminaire  
842 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	27.40	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic dimmable DALI		

### Physical

<b>Color</b>	Copper
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.99
<b>Spot diameter (mm)</b>	145

### Note

Pre-installation frame. To be ordered separately.

## Kap Ø145 Deep Dali



---

Installation Frame Trim  
08.8491.BU




---

Installation Frame Trim  
08.8491.14



---

Installation Frame Trim  
08.8491.30



---

Installation Frame No Trim  
08.8156.00



---

Installation Frame Trim  
08.8491.GL