Kap Ø145 Wall-Washer 1-10V

03.4588.BU.1V - Blue

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.



*NO TRIM
**TRIM

Main specifications

Number of heads	1	**Net lumen (lm)**	1026
Lamp category	LED	**Mountings**	Ceiling recessed
Power (W)	17W	**Environment**	Indoor
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Indirect, Direct
LED type	LED array
Light distribution	Asymmetric
Optical type	Wall-washer
Beam angle (°)	56
Beam angle C90-270 (°)	63
Efficiency (lm/W)	60



Luminous flux luminaire
1026 lm (EXTREME CUT OFF)

Beam Angle: 56°

h(m)	E(lx)	D(m)
1	1018	1.17
2	254	2.34
3	113	3.51
4	64	4.68
5	41	5.85

Electrical

Frequency (Hz)	50/60	**Emergency**	Without
Voltage (V)	27.40	**Insulation class**	II
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable 1-10V		

Physical

Color	Blue
Orientation	Fixed
Weight (kg)	0.94
Spot diameter (mm)	145

Note

Pre-installation frame. To be ordered separately.

Kap Ø145 Wall-Washer 1-10V

Installation Frame Trim
08.8491.BU

Installation Frame Trim
08.8491.14



Installation Frame No Trim
08.8251.00

Installation Frame Trim
08.8491.30

Installation Frame Trim
08.8491.GL