



Kap Ø145 Wall-Washer 1-10V

■ 03.4589.74.1V - Black

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.



*NO TRIM
**TRIM




Main specifications

Number of heads	1	Net lumen (lm)	999
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	17W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Indirect, Direct
LED type	LED array
Light distribution	Asymmetric
Optical type	Wall-washer
Beam angle (°)	55
Beam angle C90-270 (°)	63
Efficiency (lm/W)	58



Beam Angle: 55°

h(m)	E(lx)	D(m)
1	1018	1.14
2	254	2.29
3	113	3.43
4	64	4.57
5	41	5.72

Luminous flux luminaire
999 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	27.40	Insulation class	II
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic		
	dimnable 1-10V		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	0.94
Spot diameter (mm)	145

Note

Pre-installation frame. To be ordered separately.


Kap Ø145 Wall-Washer 1-10V



Installation Frame Trim
08.8491.BU



Installation Frame Trim
08.8491.14



Installation Frame No Trim
08.8251.00



Installation Frame Trim
08.8491.30



Installation Frame Trim
08.8491.GL