


## Kap Ø145 Wall-Washer Dali

03.4588.B1.DA - White

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.



\*NO TRIM  
\*\*TRIM




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1246
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	17W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Asymmetric
<b>Optical type</b>	Wall-washer
<b>Beam angle (°)</b>	56
<b>Beam angle C90-270 (°)</b>	62
<b>Efficiency (lm/W)</b>	73



<b>Beam Angle: 56°</b>		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	1145	1.17
2	286	2.34
3	127	3.52
4	72	4.69
5	46	5.86

Luminous flux luminaire  
1246 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	27.40	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic dimmable DALI		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.94
<b>Spot diameter (mm)</b>	145

### Note

Pre-installation frame. To be ordered separately.

## Kap Ø145 Wall-Washer Dali




---

Installation Frame Trim  
08.8491.BU



---

Installation Frame Trim  
08.8491.14



---

Installation Frame No Trim  
08.8251.00



---

Installation Frame Trim  
08.8491.30



---

Installation Frame Trim  
08.8491.GL