



Kap Ø50 Adjustable Optic Flood

■ 05.7317.BU - Blue

Recessed luminaire with LED light source. Power supply not included. Remote power supply to be installed in an accessible place.




Main specifications

Number of heads	1	Net lumen (lm)	463
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	7.5W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	49
Beam angle C90-270 (°)	49



Beam Angle: 49°

h(m)	E(lx)	D(m)
1	725	0.91
2	181	1.81
3	81	2.72
4	45	3.63
5	29	4.53

Luminous flux luminaire
463 lm (EXTREME CUT OFF)

Electrical

Voltage (V)	35	Emergency	Without
Current (mA)	200	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		

Certification / Marking



Physical

Color	Blue	Rotation (°)	360
Orientation	Adjustable	Spot diameter (mm)	50
Recessed depth (mm)	100	Length (mm)	54
Weight (kg)	0,162		
Tilt (°)	20		

Kap Ø50 Adjustable Optic Flood



Power supply non dimmable.
Multicurrent 125-500mA; 5,5-22W
60.9160

Continuous current power supply
dimmable 0-10V. 20W
60.9483

Continuous current power supply
dimmable DALI 220/240V – 50/60Hz.
20W – 200 mA.
60.9604



Casambi Broadcast. Remote Installation
60.9392

Continuous current power supply of
7,2-24W, 220/240V – 50/60Hz
60.9421