


## Kap Ø50 Fixed Optic Medium

■ 05.7301.74 - Black

Recessed luminaire with LED light source. Power supply not included. Remote power supply to be installed in an accessible place.




## Main specifications

|                 |       |                |                  |
|-----------------|-------|----------------|------------------|
| Number of heads | 1     | Net lumen (lm) | 443              |
| Lamp category   | LED   | Mountings      | Ceiling recessed |
| Power (W)       | 7.5W  | Environment    | Indoor           |
| CCT (K)         | 2700K |                |                  |
| CRI             | 90    |                |                  |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 24        |
| Beam angle C90-270 (°) | 24        |
| Efficiency (lm/W)      | 51        |



Beam Angle: 24°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2018  | 0.43 |
| 2    | 504   | 0.85 |
| 3    | 224   | 1.28 |
| 4    | 126   | 1.71 |
| 5    | 81    | 2.13 |

Luminous flux luminaire  
443 lm (EXTREME CUT OFF)

## Electrical

|              |                                                                                            |                  |         |
|--------------|--------------------------------------------------------------------------------------------|------------------|---------|
| Voltage (V)  | 35                                                                                         | Emergency        | Without |
| Current (mA) | 200                                                                                        | Insulation class | III     |
| Dimmable     | Yes                                                                                        |                  |         |
| Driver       | Remote                                                                                     |                  |         |
| Driver type  | Electronic,<br>Electronic dimmable,<br>Electronic dimmable 1-10V, Electronic dimmable DALI |                  |         |

## Physical

|                     |       |
|---------------------|-------|
| Color               | Black |
| Orientation         | Fixed |
| Recessed depth (mm) | 100   |
| Weight (kg)         | 0,136 |
| Spot diameter (mm)  | 54    |

## Note

Pre-installation frame. To be ordered separately.

## Kap Ø50 Fixed Optic Medium



Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200mA – 8,5W / 250mA – 11W / 300mA – 13W / 350mA – 15W / 400mA – 17,5W / 450mA 19,5W / 500mA – 22W.  
60.9160

Continuous current power supply dimmable 0-10V. 20W  
60.9483

Continuous current power supply dimmable DALI 220/240V – 50/60Hz. 20W – 200 mA.  
60.9604



Casambi Controller 220-240V. Remote Installation  
60.9392

Continuous current power supply. 220/240V – 50/60Hz. Adjustable Current 150 mA – 7,2W / 200 mA – 9,5W / 250 mA – 12W / 300 mA -14,5W / 350 mA -17W/400 mA – 19,5W / 450 mA -21,5W / 500 mA – 24W. Mains or push dimming  
60.9421

Installation frame No Trim  
08.9114.00