Kap Ø80 Adjustable Optic Spot - Dim-To-Warm

03.4538.74.LE - Black

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.



Main specifications

Number of heads	1	**Net lumen (lm)**	630
Lamp category	LED	**Mountings**	Ceiling recessed
Power (W)	13W	**Environment**	Indoor
CCT (K)	2850K-1800K		
CRI	95		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	17
Beam angle C90-270 (°)	18
Efficiency (lm/W)	48



Luminous flux luminaire
630 lm (EXTREME CUT OFF)

Beam Angle: 17°

h(m)	E(lx)	D(m)
1	2746	0.31
2	687	0.61
3	305	0.92
4	172	1.22
5	110	1.53

Electrical

Frequency (Hz)	50/60	**Driver type**	Electronic dimmable 1-10V
Voltage (V)	33.00	**Emergency**	Without
Current (mA)	300	**Insulation class**	II
Dimmable	Yes		
Driver	Remote		

Physical

Color	Black	**Rotation (°)**	360
Orientation	Adjustable	**Spot diameter (mm)**	74
Recessed depth (mm)	91		
Weight (kg)	0.24		
Tilt (°)	20		

Note

For 110V PSU versions, please consult with the front office. Diffusing lens included.

Kap Ø80 Adjustable Optic Spot - Dim-To-Warm

Installation frame No Trim
08.9102.00