



Kap Ø80 Fixed **03.4228.CU - Copper**

Recessed 12V lamp luminaire. Remote transformer not included.


Recessed 12V lamp luminaire. Remote transformer not included.

**Main specifications**

| | | | |
|-----------------|------------------|-------------|--------|
| Number of heads | 1 | Environment | Indoor |
| Lamp category | Halogen | | |
| Power (W) | 50W Max | | |
| Net lumen (lm) | 668 | | |
| Mountings | Ceiling recessed | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| Lamp type | QR-CBC 51 |
| Light distribution | Symmetric |
| Beam angle (°) | 17 |
| Beam angle C90-270 (°) | 17 |



Beam Angle: 17°

| h(m) | E(lx) | D(m) |
|------|-------|------|
|------|-------|------|

| | | |
|---|------|------|
| 1 | 5161 | 0.30 |
|---|------|------|

| | | |
|---|------|------|
| 2 | 1290 | 0.61 |
|---|------|------|

| | | |
|---|-----|------|
| 3 | 573 | 0.91 |
|---|-----|------|

| | | |
|---|-----|------|
| 4 | 323 | 1.22 |
|---|-----|------|

| | | |
|---|-----|------|
| 5 | 206 | 1.52 |
|---|-----|------|

Luminous flux luminaire
848 lm (EXTREME CUT OFF)**Electrical**


| | | | |
|----------------|--------|------------------|------------|
| Frequency (Hz) | 50/60 | Driver type | Electronic |
| Voltage (V) | 12.00 | Emergency | Without |
| Lamp holder | GX5.3 | Insulation class | III |
| Dimmable | No | | |
| Driver | Remote | | |

Physical

| | |
|---------------------|--------|
| Color | Copper |
| Orientation | Fixed |
| Recessed depth (mm) | 130 |
| Weight (kg) | 0.12 |
| Spot diameter (mm) | 74 |

Note

Not suitable for lens accessories.



Kap Ø80 Fixed



12V Electronic Transformer 20-70W for
LED Bulbs and Halogen Lamps
60.9398



12V electronic transformer. 220/240V,
50/60Hz. 35-105W
60.9424