



**Kap Ø80 Fixed Optic Flood - Dim-To-Warm**

■ 03.4532.GL.LE - Gold

Recessed luminaire with LED light source. 220-240V &amp; dimmable 1-10V power supply included.


Recessed luminaire with LED light source. 220-240V &amp; dimmable 1-10V power supply included.

**Main specifications**

|                 |             |                |                  |
|-----------------|-------------|----------------|------------------|
| Number of heads | 1           | Net lumen (lm) | 690              |
| Lamp category   | LED         | Mountings      | Ceiling recessed |
| Power (W)       | 13W         | Environment    | Indoor           |
| CCT (K)         | 2850K-1800K |                |                  |
| CRI             | 95          |                |                  |

**Optical**

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 47        |
| Beam angle C90-270 (°) | 45        |
| Efficiency (lm/W)      | 53        |



Beam Angle: 47°

|   | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 1183 | 0.87  |      |
| 2 | 296  | 1.75  |      |
| 3 | 131  | 2.62  |      |
| 4 | 74   | 3.50  |      |
| 5 | 47   | 4.37  |      |

Luminous flux luminaire  
690 lm (EXTREME CUT OFF)**Electrical**

|                |        |                  |                           |
|----------------|--------|------------------|---------------------------|
| Frequency (Hz) | 50/60  | Driver type      | Electronic dimmable 1-10V |
| Voltage (V)    | 33.00  | Emergency        | Without                   |
| Current (mA)   | 300    | Insulation class | II                        |
| Dimmable       | Yes    |                  |                           |
| Driver         | Remote |                  |                           |

**Physical**

|                     |       |
|---------------------|-------|
| Color               | Gold  |
| Orientation         | Fixed |
| Recessed depth (mm) | 91    |
| Weight (kg)         | 0.24  |
| Spot diameter (mm)  | 74    |

**Note**

For 110V PSU versions, please consult with the front office. Diffusing lens included.

## Kap Ø80 Fixed Optic Flood - Dim-To-Warm



---

Installation frame No Trim  
08.9102.00