


## Kap Ø80 Fixed Optic Medium

■ 03.4181.GL - Gold

Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.




### Main specifications

Number of heads	1	Net lumen (lm)	594
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	9.2W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	26
Beam angle C90-270 (°)	26



Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1926	0.46
2	481	0.92
3	214	1.38
4	120	1.84
5	77	2.30

Luminous flux luminaire  
594 lm (EXTREME CUT OFF)

### Electrical

Voltage (V)	17.80	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		
Emergency	Without		


### Physical

Color	Gold
Orientation	Fixed
Recessed depth (mm)	91
Weight (kg)	0.24
Spot diameter (mm)	74

### Note

Diffusing lens included.

### Certification / Marking



## Kap Ø80 Fixed Optic Medium



Installation frame No Trim  
08.9102.00



Power supply non dimmable.  
Multicurrent 125-500mA; 5,5-22W  
60.9160



Continuous current power supply of  
13-20W, 110\*/240V – 50/60Hz with  
power current selected through  
adjustable switch. Synchronisation  
cables not included.  
60.9188



Constant Current Power Supply for  
LED. Dimmable DALI. 10-20W  
60.8847



Continuous current power supply of  
12-20W, 110\*/240V – 50/60Hz with  
power current selected through  
adjustable. Regulable DALI 1 y DALI 2  
60.9222



Continuous current power supply,  
Mains dimming , 220/240V – 50/60Hz,  
10W – 500mA.  
60.9411



