



## Kap Ø80 Fixed Optic Spot

03.4531.B1 - White

Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.




## Main specifications

|                 |       |                |                  |
|-----------------|-------|----------------|------------------|
| Number of heads | 1     | Net lumen (lm) | 710              |
| Lamp category   | LED   | Mountings      | Ceiling recessed |
| Power (W)       | 9.2W  | Environment    | Indoor           |
| CCT (K)         | 2700K |                |                  |
| CRI             | 90    |                |                  |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 19        |
| Beam angle C90-270 (°) | 19        |
| Efficiency (lm/W)      | 77        |



Beam Angle: 19°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2684  | 0.34 |
| 2    | 671   | 0.68 |
| 3    | 298   | 1.02 |
| 4    | 168   | 1.36 |
| 5    | 107   | 1.70 |

Luminous flux luminaire  
710 lm (EXTREME CUT OFF)

## Electrical

|              |                                                                                            |                  |         |
|--------------|--------------------------------------------------------------------------------------------|------------------|---------|
| Voltage (V)  | 18.20                                                                                      | Emergency        | Without |
| Current (mA) | 500                                                                                        | Insulation class | III     |
| Dimmable     | Yes                                                                                        |                  |         |
| Driver       | Remote                                                                                     |                  |         |
| Driver type  | Electronic,<br>Electronic dimmable,<br>Electronic dimmable 1-10V, Electronic dimmable DALI |                  |         |

## Physical

|                     |       |
|---------------------|-------|
| Color               | White |
| Orientation         | Fixed |
| Recessed depth (mm) | 91    |
| Weight (kg)         | 0.24  |
| Spot diameter (mm)  | 74    |

## Note

Diffusing lens included.

## Kap Ø80 Fixed Optic Spot



Installation frame No Trim  
08.9102.00



Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200mA – 8,5W / 250mA – 11W / 300mA – 13W / 350mA – 15W / 400mA – 17,5W / 450mA 19,5W / 500mA – 22W.  
60.9160



Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/ 650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming  
60.9188



Continuous current power supply of 10-20W, 110/240V – 50/60Hz with power current selected through adjustable 250 mA – 10W / 350 mA – 15W / 400 mA – 17W / 450 mA – 19W / 500/550/600/700 mA – 20W, Dali 1 switch.  
60.8847



Continuous current power supply of 12-20W, 110/240V – 50/60Hz with power current selected through adjustable 350mA – 17W / 400mA – 19W / 450 / 550 / 600 / 700mA – 20W regulable Dali 1 y Dali 2  
60.9222



Continuous current power supply, Mains dimming , 220/240V – 50/60Hz, 10W – 500mA.  
60.9411



---

Continuous current power supply,  
dimmable Casambi, 220/240V –  
50/60Hz, 35W – 650mA / 36W – 700 mA.  
60.9207