


Kap Ø80 Plus Fixed Optic Flood

05.7452.B1 - White

Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.




Main specifications

| | | | |
|-----------------|-------|----------------|------------------|
| Number of heads | 1 | Net lumen (lm) | 1045 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 13.4W | Environment | Indoor |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 50 |
| Beam angle C90-270 (°) | 50 |




| | | |
|-------------|-------|------|
| Beam Angle: | 50° | |
| h(m) | E(lx) | D(m) |
| 1 | 1619 | 0.93 |
| 2 | 405 | 1.86 |
| 3 | 180 | 2.79 |
| 4 | 101 | 3.72 |
| 5 | 65 | 4.65 |

Luminous flux luminaire
1045 lm (EXTREME CUT OFF)

Electrical

| | | | |
|--------------|--|------------------|---------|
| Voltage (V) | 17,8 | Emergency | Without |
| Current (mA) | 700 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI | | |

Certification / Marking



Physical

| | | | |
|---------------------|-------|-------------|----|
| Color | White | Length (mm) | 74 |
| Orientation | Fixed | | |
| Recessed depth (mm) | 150 | | |
| Weight (kg) | 0,241 | | |
| Spot diameter (mm) | 80 | | |

Kap Ø80 Plus Fixed Optic Flood



Installation frame No Trim
08.9102.00



Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch.
60.9592



Continuous current power supply of 13-20W, 110*/240V – 50/60Hz with power current selected through adjustable switch. Synchronisation cables not included.
60.9188



Constant Current Power Supply for LED. Dimmable DALI. 10-20W
60.8847



Continuous current power supply of 12-20W, 110*/240V – 50/60Hz with power current selected through adjustable. Regulable DALI 1 y DALI 2
60.9222



Continuous current power supply, Mains dimming 220/240V – 50/60Hz, 12-20W
60.9467



