


## Kap Ø80 Plus Fixed Optic Spot

■ 05.7450.74 - Black

Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.




## Main specifications

Number of heads	1	Net lumen (lm)	955
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	13.4W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

## Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	19
Beam angle C90-270 (°)	19
Efficiency (lm/W)	71



Beam Angle: 19°

h(m)	E(lx)	D(m)
1	4088	0.33
2	1022	0.66
3	454	0.99
4	255	1.31
5	164	1.64


Luminous flux luminaire  
955 lm (EXTREME CUT OFF)

## Electrical

Voltage (V)	17,8	Emergency	Without
Current (mA)	700	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		

## Physical

Color	Black
Orientation	Fixed
Recessed depth (mm)	150
Weight (kg)	0,241
Spot diameter (mm)	74



# Kap Ø80 Plus Fixed Optic Spot



Installation frame No Trim  
08.9102.00



Non dimmable continuous current  
power supply. 15-30W, 220/240V  
-50/60Hz with power currentselected  
through adjustableswitch.  
60.9592



Continuous current power supply of  
13-20W, 110\*/240V – 50/60Hz with  
power current selected through  
adjustable switch. 1-10V or push  
dimming.  
60.9188



Constant Current Power Supply for  
LED. Dimmable DALI. 10-20W  
60.8847



Continuous current power supply of  
12-20W, 110\*/240V – 50/60Hz with  
power current selected through  
adjustable. Reguable DALI 1 y DALI 2  
60.9222



Continuous current power supply,  
Mains dimming 220/240V – 50/60Hz, 12-  
20W  
60.9467



50/60Hz, 35W – 650mA / 36W – 700 mA.  
60.9207