





Kap Ø80 Plus Fixed Optic Spot

05.7451.CU - Copper

Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.




Main specifications

Number of heads	1	Net lumen (lm)	1000
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	13.4W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	22
Beam angle C90-270 (°)	22
Efficiency (lm/W)	74



Beam Angle: 22°

h(m)	E(lx)	D(m)
1	3979	0.40
2	995	0.79
3	442	1.19
4	249	1.58
5	159	1.98

Luminous flux luminaire
1000 lm (EXTREME CUT OFF)

Electrical

Voltage (V)	17,8	Emergency	Without
Current (mA)	700	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		

Physical

Color	Copper
Orientation	Fixed
Recessed depth (mm)	150
Weight (kg)	0,241
Spot diameter (mm)	74

Kap Ø80 Plus Fixed Optic Spot



Installation frame No Trim
08.9102.00



Non dimmable continuous current
power supply. 15-30W, 220/240V
-50/60Hz with power currentselected
through adjustableswitch.
60.9592



Continuous current power supply of
13-20W, 110*/240V – 50/60Hz with
power current selected through
adjustable switch. 1-10V or push
dimming.
60.9188



Constant Current Power Supply for
LED. Dimmable DALI. 10-20W
60.8847



Continuous current power supply of
12-20W, 110*/240V – 50/60Hz with
power current selected through
adjustable. Reguable DALI 1 y DALI 2
60.9222



Continuous current power supply,
Mains dimming 220/240V – 50/60Hz, 12-
20W
60.9467



50/60Hz, 35W – 650mA / 36W – 700 mA.
60.9207