





Kap Ø80 Plus Wall-Washer

 05.7420.GL - Gold

Recessed luminaire with LED light source. Power supply not included. Elliptical lens included.




Main specifications

Number of heads	1	Net lumen (lm)	861
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	13.4W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Asymmetric
Optical type	Wall-washer
Beam angle (°)	30
Beam angle C90-270 (°)	36
Efficiency (lm/W)	64



Beam Angle: 30°

h(m)	E(lx)	D(m)
1	1371	0.67
2	343	1.33
3	152	2.00
4	86	2.67
5	55	3.33

Luminous flux luminaire
861 lm (EXTREME CUT OFF)

Electrical

Voltage (V)	17,8	Emergency	Without
Current (mA)	700	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1- 10V, Electronic dimmable DALI		

Physical

Color	Gold
Orientation	Fixed
Recessed depth (mm)	150
Weight (kg)	0,241
Spot diameter (mm)	74

Kap Ø80 Plus Wall-Washer



Installation frame No Trim
08.9102.00



Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch.
60.9592



Continuous current power supply of 13-20W, 110*/240V – 50/60Hz with power current selected through adjustable switch. 1-10V or push dimming.
60.9188



Constant Current Power Supply for LED. Dimmable DALI. 10-20W
60.8847



Continuous current power supply of 12-20W, 110*/240V – 50/60Hz with power current selected through adjustable. Regurable DALI 1 y DALI 2
60.9222



Continuous current power supply, Mains dimming 220/240V – 50/60Hz, 12-20W
60.9467



50/60Hz, 35W – 650mA / 36W – 700 mA.
60.9207