



## Kap Ø80 Plus Wall-Washer

■ 05.7421.CU - Copper

Recessed luminaire with LED light source. Power supply not included. Elliptical lens included.




### Main specifications

Number of heads	1	Net lumen (lm)	882
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	13.4W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Asymmetric Wall-washer
Optical type	Wall-washer
Beam angle (°)	28
Beam angle C90-270 (°)	43
Efficiency (lm/W)	65



Beam Angle: 28°

h(m)	E(lx)	D(m)
1	1334	0.64
2	333	1.27
3	148	1.91
4	83	2.55
5	53	3.19

Luminous flux luminaire  
882 lm (EXTREME CUT OFF)

### Electrical

Voltage (V)	17,8	Emergency	Without
Current (mA)	700	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		

### Physical

Color	Copper
Orientation	Fixed
Recessed depth (mm)	150
Weight (kg)	0,241
Spot diameter (mm)	74

## Kap Ø80 Plus Wall-Washer



---

Installation frame No Trim  
08.9102.00



---

Non dimmable continuous current  
power supply. 15-30W, 220/240V  
-50/60Hz with power current selected  
through adjustable switch.  
60.9592



---

Continuous current power supply of  
13-20W, 110\*/240V – 50/60Hz with  
power current selected through  
adjustable switch. 1-10V or push  
dimming.  
60.9188



---

Constant Current Power Supply for  
LED. Dimmable DALI. 10-20W  
60.8847



---

Continuous current power supply of  
12-20W, 110\*/240V – 50/60Hz with  
power current selected through  
adjustable. Regulable DALI 1 y DALI 2  
60.9222



---

Continuous current power supply,  
Mains dimming 220/240V – 50/60Hz, 12-  
20W  
60.9467



50/60Hz, 35W – 650mA / 36W – 700 mA.  
60.9207