





Kap Ø80 Plus Wall-Washer

 05.7421.GL - Gold

Recessed luminaire with LED light source. Power supply not included. Elliptical lens included.




Main specifications

| | | | |
|-----------------|-------|----------------|------------------|
| Number of heads | 1 | Net lumen (lm) | 838 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 13.4W | Environment | Indoor |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-------------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Asymmetric |
| Optical type | Wall-washer |
| Beam angle (°) | 30 |
| Beam angle C90-270 (°) | 36 |
| Efficiency (lm/W) | 62 |



Beam Angle: 30°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 1334 | 0.67 |
| 2 | 333 | 1.33 |
| 3 | 148 | 2.00 |
| 4 | 83 | 2.67 |
| 5 | 53 | 3.33 |

Luminous flux luminaire
838 lm (EXTREME CUT OFF)

Electrical

| | | | |
|--------------|---|------------------|---------|
| Voltage (V) | 17,8 | Emergency | Without |
| Current (mA) | 700 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | Electronic, Electronic dimmable, Electronic dimmable 1- 10V, Electronic dimmable DALI | | |

Physical

| | |
|---------------------|-------|
| Color | Gold |
| Orientation | Fixed |
| Recessed depth (mm) | 150 |
| Weight (kg) | 0,241 |
| Spot diameter (mm) | 74 |

Kap Ø80 Plus Wall-Washer



Installation frame No Trim
08.9102.00



Non dimmable continuous current
power supply. 15-30W, 220/240V
-50/60Hz with power currentselected
through adjustableswitch.
60.9592



Continuous current power supply of
13-20W, 110*/240V – 50/60Hz with
power current selected through
adjustable switch. 1-10V or push
dimming.
60.9188



Constant Current Power Supply for
LED. Dimmable DALI. 10-20W
60.8847



Continuous current power supply of
12-20W, 110*/240V – 50/60Hz with
power current selected through
adjustable. Reguable DALI 1 y DALI 2
60.9222



Continuous current power supply,
Mains dimming 220/240V – 50/60Hz, 12-
20W
60.9467



50/60Hz, 35W – 650mA / 36W – 700 mA.
60.9207