

Kap Surface Ceiling Ø 100**03.4520.B3B - Brown/White**


Luminaire for mounting in ceiling with LED light source. non-regulable 110/240V, 50-60hz power supply integrated in luminaire body.

**Main specifications**

Number of heads	1	CRI	80
Lamp category	LED	Net lumen (lm)	550
Power (W)	9W	Mountings	Ceiling surface
System power (W)	11W	Environment	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	29
Beam angle C90-270 (°)	29



Beam Angle: 29°

h(m)	E(lx)	D(m)
------	-------	------

1	1482	0.52
---	------	------

2	371	1.04
---	-----	------

3	165	1.56
---	-----	------

4	93	2.08
---	----	------

5	59	2.61
---	----	------

Luminous flux luminaire
550 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	110/240	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

Physical

Color	Brown/White
Orientation	Fixed
Weight (kg)	1.50
Spot diameter (mm)	100
Length (mm)	100

