


## Kap Surface Ceiling Ø100

■ ■ 03.4522.ASB - Brushed Aluminium/Blue

Luminaire for mounting in ceiling with led light source. non-regulable 110/240V, 50-60hz power supply integrated in luminaire body.




### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	417
Power (W)	9W	Mountings	Ceiling surface
System power (W)	11W	Environment	Indoor
CCT (K)	3000K		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	28
Beam angle C90-270 (°)	28



Beam Angle: 28°

	h(m)	E(lx)	D(m)
1	1448	0.51	
2	362	1.02	
3	161	1.52	
4	91	2.03	
5	58	2.54	

Luminous flux luminaire  
417 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	110/240	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		

### Physical

Color	Brushed Aluminium/Blue
Orientation	Fixed
Weight (kg)	1.50
Spot diameter (mm)	100
Length (mm)	100

### Certification / Marking

